



WHITE SPIRIT

MS-T-200

APPLICATION

- 1- A common organic solvent in paint, Aerosols, wood preservatives, lacquers, and Asphalt products.
- 2- A solvent and Diluent in Resin and Paint Industry.
- 3- A solvent for ink products.
- 4- A solvent for house hold cleaning Products.
- 5- A degreasing solvents for metals.
- 6- An additive for furniture, shoe and floor Polishes.

COMPATIBILITY

It can be used as a cost effective 'diluent in all Aromatic solvents, naphtha, petroleum Solvent, petroleum oils and other solvents.

LIMITATIONS OF LIABILITY

The information in this datasheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. We can't be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes.

PRODUCT DATA

TEST	GUARANTEE	METHOD
Appearance	Clear	ASTM D1524
Colour	+30	ASTM D156
PH at 25°C	6.5-7.5	ASTM E70
Total Sulphur	LESS THAN 0.03%	ASTM D4249
Doctor Test	Negative	ASTM D4952
Distillation - IBP	136° C	ASTM D86
FBP	Max 220° C	
Residue Vol%	Max 1.25	
Flash point	Min 36°C	ASTM D93
Specific Gravity at 15°C KG/M ³	0.775-0.785	ASTM D1298
Freezing point	LESS THAN -40°C	ASTM D2386
Viscosity at 40°C	0.810-1.25 CP	ASTM D7042
Aromatics	Less than 18%	ASTM D1319

STABILITY AND REACTIVITY

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products: Carbon dioxide and carbon monoxide may form when heated to decomposition.

Hazardous Polymerization: Will not occur.

Incompatibilities: Strong acids, strong oxidizers.

Conditions to Avoid: Heat, flames, ignition sources and incompatibles

